

INTRODUCING THE "ULTRA COMPACT" XP-3

AIR POWERED FLUX RECOVERY SYSTEM

IMPORTANT FEATURES:

- Very lightweight and compact.
- Continuously feeds recovered flux to weld nozzle **without** need of any transfer valve.
- Slag, dust and fines are automatically removed from recovered flux.
- No moving parts in air pump. Very efficient air pump produces higher vacuum; uses less air and is much quieter than most competitive models.
- Small size makes XP-3 ideal for internal vessel welding and flux recovery.
- Optional PT-x00 pressure feed tank and optional FF-3 flux feed pipe enables a continuous flux supply equal to size of feed tank (i.e., 100 lbs (45 Kg), 300 lbs (136 Kg), 600 lbs (272 Kg) or larger.)

SPECIFICATIONS:

- **Weight Empty:** 15 lbs. (6.8 Kg)
- **Dimensions:**
10.75" (27.3 cm) H x 14.5" (36.8 cm) W x 8.5" (21.6 cm) D
- **Input Power:**
Clean, dry compressed air @ 70-100 psi (5-7 bar) @ 8 cfm (226 l/min). No electrical input required.
- **Comes complete with** 4 ft. (1.21 m) hose, NZ-1 nozzle...ready for installation!

INEXPENSIVE, LIGHTWEIGHT, VERY COMPACT, RUGGED AND POWERFUL; THE XP-3 MOUNTS EASILY ONTO MOST AUTOMATIC SUBMERGED ARC WELDING EQUIPMENT.



XP-3 (shown) mounted on Lincoln Welding Equipment)

OPTIONAL ACCESSORIES:

- Hose mounting brackets; FHM-1 (linear adjustment only) FHM-1ADJ (linear and angular adjustment).
- Flux pick-up nozzles; NZ-1 CRN corner nozzle, NZ-1BUTT butt weld nozzle.
- AV-4 electric air valve.
- PT-x00 pressure feed tank. Available in 100 lbs (45 Kg), 300 lbs (136 Kg), 600 lbs (272 Kg) or larger.
- FF-3 flux feed pipe. Automatically keeps hopper full of flux. Specify 1/2", 3/4", or 1" feed hose (need PT-x00 or similar feed tank).
- Flux feed hose. Available in 1/2", 3/4", or 1" I.D. size.

For ordering information please contact:

WELD
ENGINEERING CO., INC.

34 Fruit St.
Shrewsbury, MA 01545 (U.S.A.)
Telephone: (508) 842-2224
Fax: (508) 842-3893